

SMOK®

R-KISS KIT

SMOK®

Specifications

<b>R-Kiss Mod</b>	<b>TFV8 Baby V2 Tank</b>
Material: Zinc alloy	Material: Stainless Steel
Size: 44x28x77mm	Size: 25.4x54mm
Weight: 120.3g	Weight: 65g
Power Range: 6W-200W	Capacity: 2ml
Standby Current: <500uA	Thread: 510
Charging Current: 1.8A	
Output Voltage: 0.5V-8.2V	
Resistance Range: 0.1Ω-2.5Ω (VW)	

Warranty

Note: Please carefully keep the anti-counterfeiting codes on the package. Only the activated products (refer to mod)can get after-sale service.

R-Kiss Kit Warranty Period: 6 Months from the Purchase Date.  
Within the 6 Months, some items may not be eligible for service due to misuse, damage, or other failures caused by end users. SMOK's warranty only covers manufacturer defects or premature failure. Please contact a SMOK Authorized Vendor for more information and terms of service.

The "R-Kiss Kit Customer Card" is an important proof for customers to process warranty claims, please keep it. Read the card carefully and fill it out correctly. Warranty claims must be accompanied with this card. For more warranty policies and processes, please visit our official website: <http://www.smoktech.com/support/>

User Guide

Preparation before use:

- 1) Please make sure the battery you're using corresponds with the BATTERY WARNING CARD.
- 2) Before vaping, please make sure the tank is filled with enough e-juice.

Welcome to download our APP:Vaping Tour, share your vaping experience and communicate with global vapor fans.



Mod Operations

1. Power On:  
While the device is off, quickly click Fire Key 5 times in 2s to turn it on. The screen successively displays "SMOK";
2. Vaping:  
While the device is on, hold Fire Key to vape;
3. Screen Unlocked Status:  
1) Press UP and DOWN buttons simultaneously to change color.  
2) Press UP or DOWN Button to adjust the wattage (6W-200W).
4. Power Off:  
While the device is on, quickly press Fire Key 5 times and the screen turns off, which means the device is power off.

Tank Operation

How to fill with e-liquid

- 1) Hold the tank with one hand, and use another one to press button and then move it counterclockwise.



- 2) Add e-liquid through the slot, and pay attention not to drip in into the central airflow tube.



Control air input

Rotate the adjustable airflow system to control air input.



Adjustable Airflow Ring

If you need any additional information or have any questions about the products or its use, please contact your local SMOK agent or to visit our website [www.smok-tech.com](http://www.smok-tech.com)

LEGAL DISCLAIMER

Underage sale is prohibited. Depending on your country/region's legal smoking age. 18+ and over 21+ in other countries/regions.

WARNING

This product is not intended for use by persons under legal smoking age, nonsmokers, women who are pregnant or breastfeeding, or persons with or at risk of heart disease, high blood pressure, diabetes, or taking medicine for depression or asthma.

Introduction

Vaping is not only a relaxing way but also an explanation of life style, take the new kit R-Kiss as an example, it follows the principle of KISS, which means Keep It Simple and Stupid, you can feel this from every detail of the kit. Simple two-color combination endows this mod modern style; 200W max output power can help to offer strong vapor effect; and the newly designed user interface is also a much simpler one, from which you can get detailed vaping information. The included TFV8 Baby V2 tank has three wider airflow slots, two new coils--Baby V2 A1 and Baby A2, all of which are the best choice for max vapor. Just take R-Kiss and show your attitude! Innovation keeps changing the vaping experience!

The Kit Includes:

- 1 x R-Kiss Mod
- 1 x TFV8 Baby V2 EU Tank (2ml)
- 1 x Baby V2 A1 0.17Ω Single Coil (Pre-installed)
- 1 x Baby V2 A2 0.2Ω Dual Coils
- 1 x USB Cable
- 1 x User Manual
- Spare Parts

Verification

1. Using your Smartphone or PC visit the SMOK official website: <http://www.smok-tech.com/support/>
2. Scratch off the coating of the security label on the package to reveal the 16 authentication code. Enter it into the input field on the webpage to verify. The result will be displayed after a few seconds.
3. If you have any questions, please contact SMOK via e-mail, phone or our website to get more help.

Components



Battery Installation

- 1) Open the battery cover as the picture shows;
- 2) Place the batteries into the device according to the correct directions;
- 3) Close the battery cover.




Attach Atomizer

The R-Kiss uses a spring loaded 510 connector. Please be certain that there is nothing between the Mod and the attached atomizer.

- 1) Connect the atomizer to the device and tighten it clockwise.
- 2) After the device is powered on, please press the Fire Key to vape.

VW Mode



R-Kiss's VW Mode is available for all types of atomizers.  
• In the WATT Mode, you can use UP or DOWN Button to adjust the wattage with an increase or decrease of 0.1W to get the best preferred wattage.

- 3) Close the cap carefully and firmly. Then let it stand for several minutes to get the antibacterial medical cotton completely saturated.



Replace atomizer core

Firstly, screw the drip tip and top cap off the tank, then screw the old core off the base part and replace it with a new one.



Attention

1. Before using please read the manual carefully.
2. Connect the atomizer to a power source that is suitable for its intended use.
3. Please avoid getting the e-liquid into your mouth directly.
4. To avoid e-liquid penetrating into the device and shorten its life-circle, please remove atomizer if the device is not going to be used for a long period.
5. Please refill the atomizer when the e-liquid is nearly used out to avoid dry-burning of the atomizer.
6. Please do not drop, throw or mishandle this product as the outer shell or inner components may be damaged.
7. In order to prolong the operation of your product, please keep it away from excessive temperature and humid environment.
8. Please keep this product away from children and pregnant women.



Appendix1 Key Function Table

Key	Function(Screen Unlock Status)
Fire Key	Fast click 5 times in 2s - Power On; Fast click 5 times in 2s - Power Off; Hold on - Vape;
UP	Increase the wattage (VW Mode)
DOWN	Reduce the wattage (VW Mode)
UP + DOWN	Change the color

Appendix 2 Screen Prompts Table

Prompts	Details
"SMOK"	Power on success
"SMOK"	Power off success
BATTERY LOW	Arbitrary voltage is lower than 3.2V
BATTERY HIGH	Arbitrary voltage is higher than 4.5V
NO ATOMIZER	Atomizer hasn't been detected
OHMS TOO LOW	Atomizer 's resistance is lower than 0.10Ω
OHMS TOO HIGH	Atomizer 's resistance is higher than 2.5Ω

ATOMIZER SHORT	Atomizer 's short circuit has been detected
PCBA TOO HOT	The temperature of PCBA is too high, high temperature production start running
PCBA TOO HOT	The temperature of PCBA is too high, high temperature production start running